

Material Safety Data Sheet

U.S. Department of Labor

May be used to comply with

OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

Occupational Safety and Health
Administration

(Non-Mandatory Form)

Form Approved

OMB No. 1218-0072

| | |
|--|---|
| IDENTITY <i>(As Used on Label and List)</i> Freshly Mixed Unhardened Concrete | Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that. |
|--|---|

Section I

| | |
|--|--|
| Manufacturer's Name EZform Inc. | Emergency Telephone Number 770-913-8363 |
| Address <i>(Number, Street, City, State, and ZIP Code)</i> 120 Camp St. Suite B | Telephone Number for Information 770-913-8363 |
| Loganville, GA 30052 | Date Prepared |
| | Signature of Preparer <i>(optional)</i> |

Section II - Hazard Ingredients/Identity Information

| Hazardous Components <i>(Specific Chemical Identity; Common Name(s))</i> | OSHA PEL | ACGIH TLV | Other Limits Recommended | % <i>(optional)</i> |
|--|----------|-----------|---|---------------------|
| Formula - Mixtures of Portland or blended cements, concrete aggregates and chemical admixtures. | | | | |
| Portland and blended cements: | | | | |
| <i>Tricalcium Silicate (3CaO-SiO₂)</i> | | | <i>(CAS # 12168-85-3)</i> | |
| <i>Dicalcium Silicate (2CaO-SiO₂)</i> | | | <i>(CAS # 10034-77-2)</i> | |
| <i>Tricalcium Aluminate (3CaO-Al₂O₃)</i> | | | <i>(CAS # 23042-78-3)</i> | |
| <i>Tetracalcium Aluminoferrite (4CaO-Al₂O₃-Fe₂O₃)</i> | | | <i>(CAS # 12068-35-8)</i> | |
| <i>Calcium Sulfate Dihydrate (CaSO₄-2H₂O) (Gypsum)</i> | | | <i>(CAS # 7778-18-9) PEL-TWA 15 Mg/M³ Total Dust</i> | |
| <i>Plus traces of Calcium Oxide (CaO), Magnesium Oxide (MgO), Potassium Sulfate (K₂SO₄), and Sodium Sulfate (Na₂SO₄)</i> | | | | |
| Other Ingredients: | | | | |
| <i>Concrete Aggregates, Inert gravel, sand and rocks</i> | | | | |
| <i>Admixtures may include fly ash, granulated slag and very small amounts of organic and inorganic materials which have no effect on the hazards associated with the use of the product.</i> | | | | |

Section III - Physical/Chemical Characteristics

| | | | |
|-------------------------|---|---|-------------|
| Boiling Point | <i>N/A</i> | Specific Gravity (H ₂ O = 1) | 2.28 - 2.42 |
| Vapor Pressure (mm Hg.) | <i>N/A</i> | Melting Point | <i>N/A</i> |
| Vapor Density (AIR = 1) | <i>N/A</i> | Evaporation Rate (Butyl Acetate = 1) | <i>N/A</i> |
| Solubility in Water | <i>Slight (0.01 to 1%)</i> | PH for Plastic Concrete | 12.5 |
| Appearance and Odor | <i>Gray, plastic, flowable, granular composite - Faint odor</i> | | |

Section IV - Fire and Explosion Hazard Data

| | | | | | | | |
|------------------------------------|------------|------------------|------------|-----|------------|-----|------------|
| Flash Point (Method Used) | <i>N/A</i> | Flammable Limits | <i>N/A</i> | LEL | <i>N/A</i> | UEL | <i>N/A</i> |
| Extinguishing Media | | <i>N/A</i> | | | | | |
| Special Fire Fighting Procedures | | <i>N/A</i> | | | | | |
| Unusual Fire and Explosion Hazards | | <i>N/A</i> | | | | | |

(Reproduced in June 1999 By Ohio Ready Mixed Concrete Association)

Based on OSHA 174, Sept. 1985

Section V - Reactivity Data

| | | | |
|--|----------------|----------|---|
| Stability | Unstable | | Conditions to Avoid |
| | Stable | <i>X</i> | However the product stiffens and hardens in 2 to 8 hours and is no longer hazardous |
| Incompatibility (Materials to Avoid) <i>None</i> | | | |
| Hazardous Decomposition or Byproducts Product hardens in a few hours and then does not decompose | | | |
| Hazardous Polymerization | May Occur | | Conditions to Avoid <i>None</i> |
| | Will Not Occur | <i>X</i> | |

Section VI - Health Hazard Data

| | | | |
|---|--------------------------|-------------------------------|------------------------------|
| Route(s) of Entry: | Inhalation? <i>No</i> | Skin? <i>Yes</i> | Ingestion? <i>No</i> |
| Health Hazards (Acute and Chronic) | | | |
| <i>Acute - Wet plastic, unhardened concrete can dry the skin and cause alkali burns</i> | | | |
| <i>Chronic - Hypersensitive individuals may develop an allergic dermatitis - Portland cement may contain trace amounts of chromium</i> | | | |
| Carcinogenicity: | NTP? <i>No</i> | IARC Monographs? <i>No</i> | OSHA Regulated? <i>No</i> |
| <i>Carcinogenic Potential: Concrete frequently contains crystalline silica in concentrations greater than 0.1% principally contributed by the aggregates. Respirable crystalline silica is classified by IARC (International Agency for Research on Cancer) as a known human carcinogen and by NTP (National Toxicology Program) as "reasonably anticipated to be a carcinogen." Crystalline silica in wet concrete is not respirable and does not pose a hazard when the concrete is in its plastic or unhardened state. Once concrete has hardened, long term exposure to airborne dust generated by grinding, sawing, drilling or breaking of hardened concrete, could potentially lead to hazardous exposures to workers and subsequent health related problems. Appropriate respiratory protection should be worn during these operations.</i> | | | |
| Signs and Symptoms of Exposure | | | |
| <i>Irritation of skin and burning sensation particularly when exposure is in an area of skin previously subjected to abrasion or irritation</i> | | | |
| Medical Conditions Generally Aggravated by Exposure | | | |
| <i>Open wounds or sores</i> | | | |
| Emergency and First Aid Procedures | | | |
| <i>Irrigate eyes with water. Wash exposed areas of the body with soap and water - change clothing if contaminated with wet concrete</i> | | | |

Section VII - Precautions for Safe Handling and Use

| |
|--|
| Steps to Be Taken in Case Material is Released or Spilled |
| <i>Spill does not increase hazard</i> |
| Waste Disposal Method |
| <i>Material can be retained until it hardens when it can be disposed of as a common waste</i> |
| Precautions to Be taken in Handling and Storing |
| <i>Use barrier creams, gloves, boots and clothing to protect the skin from prolonged contact with plastic concrete. Particularly avoid abrasion of the skin in contact with unhardened plastic concrete.</i> |
| Other Precautions |
| <i>Precautions must be observed because cement burns occur with little warning - little heat is sensed. Eye protection is not generally required, except when placing methods cause splash, then tight fitting goggles should be used.</i> |

Section VIII - Control Measures

| | | |
|--|----------------------------------|---------------------|
| Respiratory Protection (Specify Type) <i>Not required</i> | | |
| Ventilation <i>N/A</i> | Local Exhaust <i>None</i> | Special <i>None</i> |
| | Mechanical (General) <i>None</i> | Other <i>N/A</i> |

| | |
|--|---|
| Protective Gloves <i>Yes - waterproof</i> | Eye Protection <i>Yes - tight fitting goggles</i> |
| Other Protective Clothing or Equipment <i>Waterproof boots, long-sleeved shirt and full length trousers should be worn</i> | |
| Work/Hygienic Practices <i>Avoid contact between skin/eyes and wet/moist concrete</i> | |